

# Business Display Solutions

## EIZO FlexScan L367

The new range of design and performance features introduced by the FlexScan L367 clearly establish EIZO's next generation MultiEdge series as the high-end choice of display for today's business, back office and administrative users.

The inclusion of EIZO original functions such as Fine Contrast, Gamma Correction, and DesktopViewer, as well as support for Seiko Epson Corporation's PRINT Image Matching (PIM) II technology deliver the high-precision image control required by complex text and graphics-based applications. Advanced capabilities like digital/analog inputs, 250 cd/m<sup>2</sup> brightness, and 450:1 contrast ratio are complemented by a wealth of ergonomic refinements that successfully integrate higher levels of functionality with even greater ease of use.

### Further 40% Reduction in Bezel Width

With ultra-slim side bezels only 10 mm wide, the newly designed cabinet is more space-efficient than ever. Navigating is easier too — control buttons are now arranged in a simple cross pattern, and set on a 3-tier front operating panel.

### Incorporated Height Adjustable Deskstand

The desktop stand is height adjustable over a range of 50 mm, or you can recover the whole desktop by utilising the VESA compliant mounting bracket.

### Fine Contrast

A one-touch button on the front panel accesses five specialised image adjustment modes: Text, Picture, Movie, Custom and sRGB, each with its own settings for parameters such as colour temperature, brightness and saturation. Using the bundled ScreenManager Pro for LCD<sup>1</sup> software's Auto Fine Contrast function, any mode can be assigned to a given application so that when the application is opened, the screen changes automatically to that mode.

### Desktop Viewer

This EIZO-designed utility<sup>2</sup> can display a JPG, BMP or TIFF image, or any selected part of the screen, in an overlay window to a maximum brightness of 250 cd/m<sup>2</sup>, as well as enlarging or reducing it and freely altering its brightness, contrast, saturation, hue and gamma values<sup>3</sup>.



### PIM II and EXIF 2.2

Both of these image optimisation technologies are supported by the FlexScan L367, enabling digital camera images to be viewed, edited and printed out at the highest level of quality. (Digital camera and printer must be PIM II and Exif 2.2-enabled)

### Gamma Correction

Internal circuitry automatically converts 8-bit data from the PC to 10-bit and back to 8-bit, producing smooth, accurate colour tones. Gamma values are also user adjustable from 1.4 to 3.0 in increments of 0.2

### Regulatory Standards

The FlexScan L367 complies with current international standards relating to safety, ergonomics and power management as well as "EIZO Eco Products 2002" an in house label covering such environmental issues as manufacture with lead free solder and chrome free steel plates.

### Screen Administrator

This EIZO-developed software enables various important setup and management tasks of client PCs and monitors to be executed across a network from a single server PC.

# Business Display Solutions

## L367 Specifications

Panel Type	38cm (15.1") Colour LCD Panel
Dot Pitch	0.297mm x 0.297mm
Display Colour	16.7 Million Colours
Viewing Angle	H: 160° V: 150°
Scanning Frequency (Analog)	H: 24.8-61kHz, 55-75 Hz
Scanning Frequency (Digital)	H: 31-61kHz V: 59-61Hz (VGA Text: 69-71Hz)
Native Resolution	1024 x 768
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	450:1
Response Time	Rise Time: 6ms, Fall Time: 19ms
Dot Clock	Analog: 80MHz, Digital: 65MHz
Input Signals	RGB Analog, DVI Digital
Input Terminals	1 x D-Sub mini 15 pin, 1 x DVI-D
Active Display Size (HxV)	304 x 228 mm
Viewable Image Size (D)	380mm
Plug and Play <sup>1</sup>	VESA DDC 2B
Screen Control	ScreenManager, One Touch Auto Adjustment
Power Management	VESA DPMS, DVI DMPM
Power Consumption	28 Watts
Power Save Mode	Less than 3 Watts
Dimensions (WxHxD)	With Stand: 326 x 329.5-379.5 x 173mm Without Stand: 326 x 249 x 44mm
Net Weight	With Stand: 3.7kg Without Stand: 2.5kg
Certifications/Standards	TCO <sup>99</sup> *, TUV/Ergonomics, TUV/GS, c-Tick, CE, CB, UL 60950: 2000, CSA22.2 No 60950-00, FCC-B, Canadian ICES-003-B, TUV/S, VCC1-B, EPA Energy Star <sup>®</sup> , EIZO Eco Products 2002
Speakers	2 x 1 watt
Supplied Accessories	AC Power Cord, signal cable (D-Sub mini 15 pin), USB cable, audio cable, setup guide, EIZO LCD Utility Disk (Screen Manager Pro for LCD, ICC Profile, HTML user's manual), 4 screws for mount option, warranty registration card



## Advanced Features

- Colour Management
- Image Scaling
- Image Smoothing
- ScreenManager<sup>®</sup>
- Auto Adjustment
- Plug and Play
- Power Manager
- Off Timer
- Freemount Option
- Sound
- DVI-D

## Options

- Grey Bezel (L367-UK)
- Black Bezel (L367K-UK)
- Flexible Mounting Arm (LA-S05-V-C)
- LCD Protection Sheets (FP-301)

<sup>1</sup> ScreenManager Pro for LCD is compatible with the Microsoft<sup>®</sup> Windows<sup>®</sup> 98SE, ME, 2000, and XP operating systems only.

<sup>2</sup> Desktop/Viewer is compatible with the Windows 2000/XP OS only.

<sup>3</sup> Support for editing functions varies with the graphics card used.

<sup>4</sup> Grey cabinet only.

Specifications are subject to change without notice. E&OE

With current LCD technology, a panel may contain a limited number of missing or flickering pixels.



This product supports PRINT Image Matching. Combination of use PRINT Image Matching and PRINT Image Matching II enabled digital still cameras, printers, and software help photographers to produce images which are more faithful to their intentions. Copyright © 2002 Eizo Nanao Corporation. All rights reserved. All product names are trademarks or registered trademarks of their respective companies. Screen Administrator is a trademark, and FlexScan, EIZO, and ScreenManager are registered trademarks of Eizo Nanao Corporation.