

▶ 20.1" LCD DISPLAY

X-20A/X-20AV



▶ FEATURES

- Distinctive aluminum and magnesium alloy housing for added strength
- NeoV Optical Filter
- Crisp 600 contrast ratio
- Super wide viewing angle technology
- DVI ready for high quality signal
- Multiple video inputs (X-20AV only)
- SRS WOW surround sound effect
- Remote control for convenient adjustment
- Cable organizer
- Kensington® security slot



▶ SPECIFICATION

| | | |
|---------------------|-------------------------------|--|
| Panel | Panel Type | TFT LCD |
| | Panel Size | 20.1" |
| | Max. Resolution | UXGA 1600 x 1200 |
| | Pixel Pitch | 0.255mm |
| | Brightness | 250cd/m ² (Typical) |
| | Contrast Ratio | 600:1 (Typical) |
| | Surface Treatments | Hard Coating (2H), anti-glare treatment |
| | Viewing Angle (H/V) | 170°/170° (Minimum) |
| | Uni-Directional | 160° (Typical) |
| | Display Color | 16.7M |
| | Response Time (R/F) | 15ms / 10ms (Typical) |
| | Frequency (H/V) | H: 30kHz - 80kHz V: 50Hz - 75Hz |
| | Max. Pixel Clock | Analog: 203MHz, DVI: 165MHz |
| | Life Time | 50,000hrs (Minimum) |
| Input | Analog | 15-Pin D-Sub |
| | Digital (DVI-D) | 29-Pin DVI |
| | S-Video (X-20AV only) | 4-Pin Mini Din S-Video |
| | CVBS (X-20AV only) | CVBS Jack |
| | Componet (X-20AV only) | 6-Pin Mini Din Componet |
| Audio | Audio In | 3.5mm audio line-in |
| | Audio Out | 3.5mm audio line-out |
| | Processor Effect | SRS WOW |
| Connector | Power | 3-Pin AC Plug |
| NeoV Optical Filter | Thickness | 3.0mm (0.18") |
| | Reflection Rate | <1% |
| | Transmission Rate | >96% |
| | Hardness | >6H (MOH's Rating) |
| Tilt | Tilt | 0° ~ 15° |
| Mounting | VESA FPMPI | Yes (100mm) |
| Dimensions | Net (W x H x D) | 499 x 454 x 180 mm (19.7" x 17.9" x 7.1") |
| | Packing (W x H x D) | 570 x 594 x 261 mm (22.4" x 23.4" x 10.1") |
| Weight | Net Weight | 10.1Kg (22.3lbs) |
| | Gross Weight | 11.7Kg (25.3lbs) |
| Regulation Approval | Safety & EMI | FCC, CE, VCCI, BSMI, CCC, TUV/BAURT, UL/CUL, TCO 95, CB, ISO 13406-2 |
| | VESA | DDC 1/2B, DPMS |
| Power | Power AC Consumption | 100 - 240V, 50 - 60Hz <80W (On) <5W (Stand-by) <5W (Off) |

* All specifications are subject to change without prior notice.

▶ CONTACT INFORMATION

Global Headquarters

Associated Industries China, Inc.
T: 886-2-2357-5896
F: 886-2-3393-2475
www.neovo.com

Europe

AG Neovo Technology B.V.
T: 31-10-442-57-37
F: 31-10-442-57-42
www.agneovo.nl

North & South America

AG Neovo Technology Corp.
T: 1-408-321-8210
F: 1-408-321-8211
www.neovo-usa.com

Asia Pacific & Middle East

Associated Industries China, Inc.
T: 886-2-2357-5896
F: 886-2-3393-2475
www.neovo.com